

2026

Bias Tyre Product Manual

Quality is the root
Integrity is the foundation
Culture is the soul
Staff of Kunlun is a family



Tel:0086-0991-3304705
Fax:0086-09913391114



Add:Rongbai Wealth Building A, 886 Tong'an Road,
Laoshan District, Qingdao City, Shandong Province

About us

Xinjiang Kunlun Engineering Tire Co., Ltd. is a joint-stock enterprise controlled by Shanghai Double Coin Group Ltd., a subsidiary of Shanghai Huayi Group, and a wholly-owned subsidiary of Double Coin Group (Xinjiang) Kunlun Tire Co., Ltd. It is mainly engaged in the production and sales of various types of bias tires. It is a large-scale second-class enterprise supervised by Xinjiang Uygur Autonomous Region as well as one of the largest tire production enterprises in Northwest China.

The company, formerly Xinjiang Rubber Factory, was founded in 1971 and was listed as one of the 59 designated tire manufacturers by the Ministry of Chemical Industry. According to the relevant policies of the national pilot cities for optimizing the capital structure, the company merged Urumqi Tire Factory by way of assuming debts and changed its name to "Xinjiang Kunlun Co., Ltd." on September 23, 1997. It was renamed as "Xinjiang Kunlun Tire Co., Ltd." on December 29, 2009. It was renamed "Xinjiang Kunlun Engineering Tire Co., Ltd." in July 2011 after equity alteration and adjustment.

With a registered capital of 115 million yuan, total assets being up to 600 million yuan, an annual output of 1.2 million sets of bias tires, 200,000 sets of engineering tires, and sales revenue of more than 1 billion yuan, it mainly produces and sells different variety of bias tires. At present, there are more than 200 specifications and more than 800 types of bias tires in five series, including construction machinery tires, engineering trucks tires, agricultural tires, industrial vehicles, and truck tires.

The company has always been committed to and concentrating on the development and production of a wide range of rubber tires of the best quality in China's tire industry" to make Kunlun stronger and bigger. With the domestic advanced process equipment, production organization system and mature and perfect modern management mechanism, the company keeps up with the market and continuously introduces "new, rare and special" tires to meet demands of markets. "Kunlun" tires rank first in terms of quality, reputation, market positioning throughout China, and are exported to Vietnam, Thailand, Pakistan, Indonesia and other Southeast Asia and neighboring Central Asian countries. They were awarded the first batch of "Xinjiang famous-brand products" by Xinjiang Uyghur Autonomous Region, "consumer trustworthy products" and "quality supervision and inspection-free products" and so on. "Kunlun" trademark was rated as the first batch of "Xinjiang famous trademark".

Under the leadership of Huayi Group, Double Coin Group and Xinjiang Head Office, all employees of the company will always shoulder the lofty responsibilities and missions entrusted by history, adhere to the cultural concept of "quality is the root, integrity is the foundation, culture is the soul, and the staff of Kunlun is a family", take the "specialized, refined and differentiated" road, and always follow the corporate concept of "loyalty, responsibility, integrity, double win, and being a person and enterprise respected by the society". It is committed to becoming the most professional tire manufacturer and service provider in China to provide customers with high-quality and satisfactory products. It strives to be a large enterprise group with scientific management, outstanding main business, excellent innovation ability, independent brand and strong core competitiveness.

Contents

AGRICULTURAL RADIAL TIRE SERIES-----	1-4
AGRICULTURAL MACHINERY TIRE SERIES-----	5-6
AGRICULTURAL TIRE SERIES-----	7-18
PORT TIRE SERIES-----	19-22
INDUSTRIAL VEHICLE TIRE SERIES-----	23-26
CONSTRUCTION MACHINERY TIRE SERIES-----	27-34
TRUCK TIRE SERIES-----	35-40
ENGINEERING TRUCK TIRE SERIES -----	41-44
LIGHT TRUCK TIRE SERIES-----	45-52
ATTACHMENT-----	53-57
CORPORATE HONORS-----	58



AGRICULTURAL RADIAL TIRE SERIES

KT179 R-1W

Product performance :

- Strong driving force, excellent bearing capacity, scientific design of block patterns and excellent tire shoulder design, with super traction;
- Excellent self-cleaning, protecting soil, level ground contact and low pressure, good soil recovery;
- Super wear-resistance, long service life.



Size	Tube Type	Tread Depth(mm)	Rim	New tire size(mm)		Load index	Load Capacity(kg)	Inflation Pressire (kpa)
				OD	SW			
480/70R28	TL	41.0	W15L	1421	479	140D	2500	160
540/65R30	TL	50.0	W18L	1464	550	143D	2725	160
650/65R38	TL	51.0	DW20A	1811	645	157 A8 157/B	4125	160

KT178 R-1W (90/85/80)

Product performance :

- Strong driving force, excellent bearing capacity, scientific design of block patterns and excellent tire shoulder design, with super traction;
- Excellent self-cleaning, protecting soil, level ground contact and low pressure, good soil recovery;
- Super wear-resistance, long service life.



Size	Tube Type	Tread Depth(mm)	Rim	New tire size(mm)		Load index	Load Capacity(kg)	Inflation Pressire (kpa)
				OD	SW			
300/80R15.3	TL	26.5	W9	869	295	129A8 141 B	1850	400
440/80R28	TL	45.0	DW14L	1415	441	156A8 156B	4000	320
480/80R38	TL	50.0	W15	1733	479	151A8 151 B	3450	200
IF580/80R34	TL	53.0	DW20B	1792	576	177A8 177 B	7300	360
280/85R20	TL	40.0	W9	984	282	112A8 112 B	1120	160
320/85R24	TL	42.0	W10	1154	319	161A8 164 B	1500	160
340/85R24	TL	41.0	W11	1188	343	125A8 122 B	1650	160
380/85R24	TL	44.0	W12	1256	380	131A8 131 B	1950	160
380/85R28	TL	46.0	W12	1357	380	133A8 133 B	2060	160
380/85R30	TL	42.0	W12	1408	380	135A8 135 B	2180	160
420/85R24	TL	48.0	W15L	1324	418	137 D	2300	160
420/85R28	TL	45.0	W13	1425	418	139A8 139 B	2430	160
420/85R30	TL	46.0	W15L	1476	418	140 D 140A8	2500	160
420/85R34	TL	48.0	W15L	1578	418	147A8 147 B	3075	240
460/85R30	TL	48.0	DW15L	1544	455	154A8	3750	240
460/85R38	TL	48.0	W14L	1747	455	149A8 149 B	3250	160
520/85R38	TL	51.0	DW16L	1849	516	155A8 155 B	3875	160
520/85R42	TL	54.0	DW16L	1951	516	162A8 162 B	4750	240
IF520/85R42	TL	53.0	DW18L	1951	526	169A8 169 B	5800	240
650/85R38	TL	56.0	DW20B	2071	645	173 D 173A8	6500	240
420/90R30	TL	45.0	DW13	1518	418	143 D 147A8	3075	240

KT178

R-1W (75/70/65)

Product performance :

- Strong driving force, excellent bearing capacity, scientific design of block patterns and excellent tire shoulder design, with super traction;
- Excellent self-cleaning, protecting soil, level ground contact and low pressure, good soil recovery;
- Super wear-resistance, long service life.



Size	Tube Type	Tread Depth(mm)	Rim	New tire size(mm)		Load index	Load Capacity(kg)	Inflation Pressire (kpa)
				OD	SW			
540/65R28	TL	48.0	W18L	1413	550	142 D 145A8	2650	160
540/65R30	TL	50.0	W18L	1464	550	143 D	2725	160
600/65R38	TL	50.0	DW18A	1745	601	159 D	4375	240
650/65R38	TL	51.0	DW20A	1811	645	157A8 157 B	4125	160
650/65R42	TL	50.0	DW20A	1913	645	165 D 168A8	5150	240
IF800/65R32 CFO	TL	58.0	DW27B	1853	798	181 D	8250	280
260/70R16	TL	29.0	W8	770	258	109 D	1030	240
VF265/70R15.3	TL	24.0	9.00*15.3	760	265	124A8 124 B	1600	280
280/70R16	TL	42.0	W9	798	282	112 D 112A8	1120	240
280/70R18	TL	36.0	W9	849	282	114 D 117A8	1180	240
280/70R20	TL	33.0	W9	900	282	116 D	1250	240
320/70R20	TL	39.0	W10	982	319	130 D 133A8	1900	320
15R24	TL	30.0	DW14L	1330	406	148A8 148 B	3150	330
380/70R24	TL	42.0	W12	1190	380	125 A8/B 130A8/D	1650 1900	160 240
480/70R24	TL	45.0	W15L	1316	479	155 D 158A8	3875	420
360/70R28	TL	41.0	W11	1251	357	125A8 130 D	1900	240
380/70R28	TL	42.0	W12	1293	380	127 D	1750	160
600/70R28	TL	50.0	DW18L	1551	601	157A8 157 B	4125	240
600/70R30	TL	51.0	DW18L	1602	591	158A8 158 B	4250	240
520/70R38	TL	49.0	DW16L	1749	516	150 D	3350	160
710/70R38	TL	51.0	DW23A	1959	716	171A8 171 B	6150	240
IF800/70R38	TL	62.0	DW27B	2085	804	184 D	9000	240
580/70R42	TL	52.0	DW18L	1879	577	158A8 158 B	4250	160
IF710/70R42	TL	52.0	DW25B	2061	705	179A8 179 B	7750	240
620/75R26	TL	53.0	DW20B	1590	625	166 D	5300	320
620/75R34	TL	51.0	DW20B	1794	625	170A8 170 B	6420	320

KT755

Product performance :

- A larger ground contact area effectively protects the soil;
- High-saturation pattern provides superior wear resistance and puncture resistance;
- The body has a high strength and a higher load-bearing capacity.
- With efficient operation, fuel-saving performance and s strong gripping force, this kind of tire is suitable for various agricultural machinery and equipment.



Size	Tube Type	Tread Depth(mm)	Rim	New tire size(mm)		Load index	Load Capacity(kg)	Inflation Pressire (kpa)
				OD	SW			
340/80R20	TL	28.0	11	1052	343	144A8 141 B	2800	400
400/70R20	TL	29.0	13	1068	404	149 A8 149 B	3250	400
500/70R24	TL	38.0	DW16L	1310	503	164 A8 161 B	5000	400
540/70R24	TL	36.0	DW18L	1366	540	149 A8 158 B	3250	400

KT181

R-2

Product performance :

- Deep pattern in design, super driving force and traction, and bearing capacity;
- Super wear resistance, long service life.



Size	Tube Type	Tread Depth(mm)	Rim	New tire size(mm)		Load index	Load Capacity(kg)	Inflation Pressire (kpa)
				OD	SW			
540/65R30	TL	78.0	W18L	1464	540	150 A8 150/B	3350kg	240kpa



AGRICULTURAL MACHINERY TIRE SERIES

KT755 (R-4)

Product performance :

- A larger ground contact area effectively protects the soil;
- High-saturation pattern provides superior wear resistance and puncture resistance;
- The body has a high strength and a higher load-bearing capacity.
- With efficient operation, fuel-saving performance and s strong gripping force, this kind of tire is suitable for various agricultural machinery and equipment.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressire (kpa)
					OD	SW		
500/50-17	TL	21.0	16.00	18PR	932	503	3000/4125	400
400/60-15.5	TL	15.5	AG13.00	14PR	874	404	2900	350

KT8D (I-1)

Product performance :

- Excellent load bearing performance and wear resistance;
- Reasonable pattern design and good guiding performance;
- Higher strength and excellent resistance to deflection and aging.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressire (kpa)
					OD	SW		
☆10-15	TT	8.5	9.00	10PR	855	286	1525	390

KT58 (I-1)

Product performance :

- Excellent load bearing performance and wear resistance;
- Reasonable pattern design and good guiding performance;
- Higher strength and excellent resistance to deflection and aging.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressire (kpa)
					OD	SW		
10.0/75-15.3	TT	10.0	9.00	10PR	760	264	1525	390

KT5 (R-1)

Product performance :

- Large pattern angles can prevent the tire pattern root from deflecting and deforming, and improve the service life of tires;
- Good traction and self-cleaning performance;
- Higher strength and excellent wear resistance.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressire (kpa)
					OD	SW		
10.0/75-15.3	TT	23.5	9.00	12PR	760	264	1700	470



KT676 (R-1)



Product performance :

- Large pattern angles can prevent the tire pattern root from deflecting and deforming, and improve the service life of tires;
- Good traction and self-cleaning performance;
- Higher strength and excellent wear resistance.

Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressire (kpa)
					OD	SW		
☆10/75-15.3	TT	24.5	9.00	10PR	910	315	1525	390

KT100S



Product performance :

- Smooth surface in design produces less resistance;
- Anti-puncture tire side design is more suitable for operation in farms with straws.

Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressire (kpa)
					OD	SW		
10/75-15.3	TT	/	9.00	12PR	736	264	2500	470

KT6

Product performance :

- Large pattern angles can prevent the tire pattern root from deflecting and deforming, and improve the service life of tires;
- Good traction and self-cleaning performance;
- Higher strength and excellent wear resistance.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressire (kpa)
					OD	SW		
31×15.50-15	TL	19.0	13.00	12PR	792	391	1680	520

KT566 (CR-1)

Product performance :

•Differentiated pattern design, better tire wear resistance; excellent puncture resistance and driving performance. This type of tire is suitable for harvesting machinery operating in fields.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressire (kpa)
					OD	SW		
☆12.00-18	TT	16.0	9.00V	12PR	1090	327	2300	420

KT66 (R-1)

Product performance :

•With strong gripping force, excellent puncture resistance, good wear resistance, good driving performance, this type of tire is suitable for operation in fields.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressire (kpa)
					OD	SW		
8.3-20	TT	28.0	W7	8PR	895	210	850	310
8.3-20	TT	28.0	W7	10PR	895	210	780	300
12.4-28	TT	33.0	W11	10PR	1260	315	1725	300
12.4-28	TT	33.0	W11	12PR	1260	315	1950	340
13.6-28	TT	35.0	W12	8PR	1310	345	1645	210
13.6-28	TT	35.0	W12	10PR	1310	345	1910	250
13.6-28	TT	35.0	W12	12PR	1310	345	2170	280
15-24	TT	31.0	DW14	10PR	1330	410	2800	280
15-24	TT	31.0	DW14	12PR	1330	410	3100	330
15-24	TT	31.0	DW14	14PR	1330	410	3500	410
18.4-34	TT	37.0	W16L	10PR	1655	467	2990	180
18.4-34	TT	37.0	W16L	12PR	1655	467	3375	230
18.4-34	TT	37.0	W16L	14PR	1655	467	3630	260
20.8-38	TT	40.0	W18L	10PR	1835	528	3475	160
20.8-38	TT	40.0	W18L	12PR	1835	528	4000	200
20.8-38	TT	40.0	W18L	16PR	1835	528	4800	280
20.8-38	TT	40.0	W18L	20PR	1835	528	6000	400

KT7D (R-1)

Product performance :

•With strong gripping force, excellent puncture resistance, good wear resistance, good driving performance, this type of tire is suitable for operation in fields.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressire (kpa)
					OD	SW		
☆15L-24	TT	38.0	W12	14PR	1160	365	2300	280
23.1-26	TT	41.0	DW20	12PR	1605	587	3610	170
23.1-26	TT	41.0	DW20	18PR	1605	587	4840	280

KT6 (R-1)

Product performance :

•With strong gripping force, excellent puncture resistance, good wear resistance, good driving performance, this type of tire is suitable for operation in fields.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressire (kpa)
					OD	SW		
7.50-20	TT	26.0	5.50F	8PR	910	205	760	210
8.3-24	TT	30.0	W7	8PR	995	210	830	250
☆9.5-16	TT	31.0	W8L	8PR	855	255	830	280
11.2-24	TT	33.0	W10	8PR	1105	285	1225	240
11.2-24	TT	33.0	W10	10PR	1105	285	1380	300
12.4-24	TT	34.0	W11	6PR	1160	315	1200	170
12.4-24	TT	34.0	W11	8PR	1160	315	1415	230
12.4-24	TT	34.0	W11	10PR	1160	315	1500	280
☆13.6-20	TT	32.0	W12	8PR	900	345	830	280
14.9-24	TT	32.0	W13	8PR	1265	378	1760	180
14.9-24	TT	32.0	W13	10PR	1265	378	1990	230
14.9-24	TT	32.0	W13	16PR	1265	378	2500	270

KT5 (R-1)

Product performance :

•With strong gripping force, excellent puncture resistance, good wear resistance, good driving performance, this type of tire is suitable for operation in fields.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressire (kpa)
					OD	SW		
5.00-12	TT	23.0	4.00E	6PR	590	145	350	270
6.00-12	TT	23.0	4.50E	6PR	640	165	405	250
6.00-12	TT	23.0	4.50E	10PR	640	165	420	260
6.50-16	TT	24.0	5.00F	6PR	765	180	565	250
6.50-16	TT	24.0	5.00F	8PR	765	180	630	270
7.50-16	TT	25.0	5.50F	6PR	810	205	650	210
7.50-16	TT	25.0	5.50F	8PR	810	205	770	280
12-38	TT	36.0	DW11	8PR	1575	330	1570	140
12-38	TT	36.0	DW11	10PR	1575	330	1800	220
12-38	TT	36.0	DW11	12PR	1575	330	2500	260

KT69 (R-1)

Product performance :

•With strong gripping force, excellent puncture resistance, good wear resistance, good driving performance, this type of tire is suitable for operation in fields.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressire (kpa)
					OD	SW		
☆7.00-12	TT	27.0	4.50E	8PR	665	192	480	250
☆13.6-16	TT	31.5	W12	10PR	955	345	1300	340
12.4-28	TT	41.0	W11	8PR	1260	315	1510	230
12.4-28	TT	41.0	W11	10PR	1260	315	1725	300
12.4-28	TT	41.0	W11	12PR	1260	315	1950	340
14.9-28	TT	38.0	W13	10PR	1365	378	2120	230
14.9-28	TT	38.0	W13	12PR	1365	378	2120	230
16.9-30	TT	37.0	W15L	12PR	1485	430	2730	240
16.9-30	TT	37.0	W15L	14PR	1485	430	2940	270
18.4-30	TT	40.0	W16L	10PR	1550	467	2815	180
18.4-30	TT	40.0	W16L	12PR	1550	467	3180	230
18.4-30	TT	40.0	W16L	14PR	1550	467	3705	290

KT4D (I-1)

Product performance :

•Super puncture resistance, wear resistance, and guiding performance.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressire (kpa)
					OD	SW		
4.00-16	TT	11.0	3.00D	4PR	640	110	300	340
4.00-16	TT	11.0	3.00D	6PR	640	110	325	400
5.00-15	TT	10.0	4J	6PR	665	140	465	420
5.00-16	TT	10.0	3.00D	8PR	685	140	550	420
5.50-16	TT	14.0	4.00E	8PR	710	150	600	490
6.00-16	TT	12.0	4.00E	8PR	740	160	675	450

KT2D (I-1)

Product performance :

•Super puncture resistance, wear resistance, and guiding performance.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressire (kpa)
					OD	SW		
6.50-20	TT	14.0	5.00F	8PR	860	180	865	420

KT676 (R-1)

Product performance :

•With strong gripping force, excellent puncture resistance, good wear resistance, good driving performance, this type of tire is suitable for operation in fields.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressire (kpa)
					OD	SW		
7.50-16	TT	30.0	5.50F	8PR	810	205	770	280
7.50-16	TT	30.0	5.50F	10PR	810	205	920	360
9.5-32	TT	31.0	W8	8PR	1250	240	1260	280
9.5-32	TT	31.0	W8	10PR	1250	240	1300	300
11-32	TT	32.0	W10	10PR	1460	305	1700	240
11-38	TT	32.5	W10	8PR	1540	305	1800	180
11-38	TT	32.5	W10	12PR	1540	305	2495	250
11.2-28	TT	33.0	W10	8PR	1205	285	1305	240
12.4-32	TT	34.0	W11	10PR	1360	315	1800	280
☆12.4-48	TT	37.0	W11	12PR	1795	315	2650	320
☆12.4-48	TT	37.0	W11	14PR	1795	315	3000	400
13.6-24	TT	35.0	W12	6PR	1210	345	1340	160
13.6-24	TT	35.0	W12	10PR	1210	345	1790	250
16.9-26	TT	36.6	W15L	10PR	1385	430	2305	200
16.9-28	TT	36.0	W15L	8PR	1435	430	2175	170
16.9-28	TT	36.0	W15L	10PR	1435	430	2380	200
16.9-28	TT	36.0	W15L	16PR	1435	430	2800	270
16.9-30	TT	36.0	W15L	10PR	1485	430	2455	200
16.9-30	TT	36.0	W15L	12PR	1485	430	2730	240
16.9-38	TT	38.0	W15L	8PR	1685	430	2520	170
16.9-38	TT	38.0	W15L	10PR	1685	430	2760	200
16.9-38	TT	38.0	W15L	12PR	1685	430	3300	240
16.9-38	TT	38.0	W15L	△22PR	1685	430	4430	450
18.4-30	TT	40.0	W16L	10PR	1550	467	2815	180
18.4-30	TT	40.0	W16L	12PR	1550	467	3180	230
18.4-30	TT	40.0	W16L	14PR	1550	467	3705	290

KT7 (R-1)

Product performance :

•With strong gripping force, excellent puncture resistance, good wear resistance, good driving performance, this type of tire is suitable for operation in fields.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressire (kpa)
					OD	SW		
6.00-16	TT	28.5	4.50E	6PR	745	165	495	250
9.5-20	TT	28.0	W8	8PR	950	240	955	280
9.5-20	TT	28.0	W8	10PR	950	240	1100	350
9.5-24	TT	31.0	W8	8PR	1050	240	1110	280
9.5-24	TT	31.0	W8	10PR	1050	240	1280	350

KT56 (R-1)

Product performance :

•With strong gripping force, excellent puncture resistance, good wear resistance, good driving performance, this type of tire is suitable for operation in fields.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressire (kpa)
					OD	SW		
6.00-16	TT	30.0	4.50E	6PR	745	165	495	250
6.00-16	TT	30.0	4.50E	8PR	745	165	550	360
6.50-16	TT	30.0	5.00F	8PR	765	180	630	270
7.50-16	TT	32.0	5.50F	8PR	810	205	770	280
7.50-16	TT	32.0	5.50F	10PR	810	205	920	360
8.3-20	TT	32.0	W7	12PR	895	210	860	320
8.3-24	TT	33.0	W7	8PR	995	210	830	250
8.3-24	TT	33.0	W7	10PR	995	210	850	260
9.5-24	TT	38.0	W8	10PR	1050	240	1280	350
11.2-24	TT	38.0	W10	10PR	1105	285	1380	300
11.2-28	TT	41.5	W10	10PR	1205	285	1470	280
11.2-28	TT	41.5	W10	12PR	1205	285	1620	240
12.4-28	TT	40.0	W11	10PR	1260	315	1725	300
12.4-28	TT	40.0	W11	12PR	1260	315	1950	340

KT67 (R-1)

Product performance :

•With strong gripping force, excellent puncture resistance, good wear resistance, good driving performance, this type of tire is suitable for operation in fields.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressure (kpa)
					OD	SW		
7.50-16	TT	30.0	5.50F	8PR	810	205	770	280
7.50-16	TT	30.0	5.50F	10PR	810	205	920	360
8.3-20	TT	32.0	W7	8PR	895	210	850	310
8.3-20	TT	32.0	W7	10PR	895	210	780	300
9.5-20	TT	30.0	W8	8PR	950	240	955	280
9.5-20	TT	30.0	W8	10PR	950	240	1100	350
9.5-24	TT	33.0	W8	8PR	1050	240	1110	280
9.5-24	TT	33.0	W8	10PR	1050	240	1280	350
11.2-24	TT	34.0	W10	8PR	1105	285	1225	240
11.2-24	TT	34.0	W10	10PR	1105	285	1380	300
12.4-24	TT	36.0	W11	6PR	1160	315	1200	170
12.4-24	TT	36.0	W11	8PR	1160	315	1415	230
12.4-24	TT	36.0	W11	10PR	1160	315	1500	280

KT59 (R-1)

Product performance :

•With strong gripping force, excellent puncture resistance, good wear resistance, good driving performance, this type of tire is suitable for operation in fields.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressure (kpa)
					OD	SW		
6.00-16	TT	30.0	4.50E	6PR	745	165	495	250
6.00-16	TT	30.0	4.50E	8PR	745	165	550	360
6.50-16	TT	30.0	5.00F	8PR	765	180	630	270
8.3-20	TT	32.0	W7	10PR	895	210	780	300
8.3-20	TT	32.0	W7	12PR	895	210	860	320
9.5-24	TT	38.0	W8	10PR	1050	240	1280	350

KT6D (R-1)

Product performance :

•With strong gripping force, excellent puncture resistance, good wear resistance, good driving performance, this type of tire is suitable for operation in fields.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressure (kpa)
					OD	SW		
9.5-28	TT	28.0	W8	10PR	1129	231	1420	320
12.4-54	TT	35.5	W11	12PR	1938	315	4000	320
14.9-26	TT	37.0	W13	8PR	1315	378	1820	180
14.9-26	TT	37.0	W13	10PR	1315	378	2055	230
14.9-28	TT	36.0	W13	10PR	1365	378	2120	230
14.9-30	TT	37.0	W13	10PR	1415	378	2190	230
18.4-38	TT	38.0	W16L	10PR	1755	467	3165	180
18.4-38	TT	38.0	W16L	12PR	1755	467	3575	230
20.8-42	TT	40.0	W18L	12PR	1935	528	3750	190
20.8-42	TT	40.0	W18L	16PR	1935	528	4700	260

KT68 (R-1)

Product performance :

•With strong gripping force, excellent puncture resistance, good wear resistance, good driving performance, this type of tire is suitable for operation in fields.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressure (kpa)
					OD	SW		
14.9-24	TT	36.0	W13	8PR	1265	378	1760	180
14.9-24	TT	36.0	W13	10PR	1265	378	1990	230
14.9-24	TT	36.0	W13	16PR	1265	378	2500	270
14.9-26	TT	38.0	W13	8PR	1315	378	1820	180
14.9-26	TT	38.0	W13	10PR	1315	378	2055	230
14.9-28	TT	36.0	W13	8PR	1365	378	1880	180
14.9-28	TT	36.0	W13	10PR	1365	378	2120	230
15.5-38	TT	33.0	W14L	8PR	1570	426	2060	180
15.5-38	TT	33.0	W14L	10PR	1570	426	2320	230
18.4-26	TT	37.0	DW16	10PR	1450	467	2645	180
18.4-38	TT	39.0	W16L	12PR	1755	467	3575	230
18.4-38	TT	39.0	W16L	20PR	1755	467	4685	390

KT171 (PR-1)

Product performance :

- Traditional large block pattern in design, and notch in tire shoulder bring high tire drainage and mud discharge performance;
- Wide tread, deeper pattern, large angle for pattern support at bottom, anti-tearing tires, super wear resistance;
- Reasonable pattern distribution can improve the traction and self-cleaning of tires. This kind of tire is extremely suitable for paddy fields and muddy agricultural area.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressire (kpa)
					OD	SW		
7.5-16	TT	75.0	5.50F	6PR	890	195	750	300
7.5-16	TT	75.0	5.50F	8PR	890	195	950	350
8.3-20	TT	80.0	W7	6PR	950	210	970	270
8.3-20	TT	80.0	W7	8PR	950	210	1210	330
9.5-20	TT	80.0	W8	8PR	1050	240	1300	280
9.5-24	TT	80.0	W8	8PR	1150	240	1740	300
11.2-24	TT	85.0	W10	6PR	1205	285	1465	210
11.2-24	TT	85.0	W10	10PR	1205	285	1830	250
12.4-28	TT	85.0	W11	8PR	1315	315	1785	200
12.4-28	TT	85.0	W11	10PR	1315	315	2230	240
11-32	TT	80.0	W10	6PR	1360	305	1080	160
11-32	TT	80.0	W10	10PR	1360	305	1280	240

KT181 (R-2)

Product performance :

- With deeper patter in design, it is suitable for paddy fields, dry fields and spraying machinery and can protect agricultural plants;
- With beautiful pattern in design, and better traction, its suitable tread is designed for inter- tilling agricultural machinery;
- With reinforced middle part, it is resistant to puncture and tearing.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressire (kpa)
					OD	SW		
11.2-20	TT	48.0	W10	12PR	970	285	1800	430
14.9-26	TT	71.0	W13	8PR	1355	378	1820	180
14.9-26	TT	71.0	W13	10PR	1355	378	2055	230
18.4-38	TT	77.0	W16L	10PR	1800	467	3165	180
18.4-38	TT	77.0	W16L	12PR	1800	467	3575	230
28L-26	TT	95.0	W18L	12PR	1615	715	3785	140
28L-26	TT	95.0	W18L	16PR	1615	715	4800	210
12.4-48	TT	59.0	W11	14PR	1845	315	3000	400

KT172 (PR-1)

Product performance :

- Traditional large block pattern in design, and notch in tire shoulder bring high tire drainage and mud discharge performance;
- Wide tread, deeper pattern, large angle for pattern support at bottom, anti-tearing tires, super wear resistance;
- Reasonable pattern distribution can improve the traction and self-cleaning of tires. This kind of tire is extremely suitable for paddy fields and muddy agricultural area.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressire (kpa)
					OD	SW		
6.5-16	TT	60.0	5.00F	8PR	1050	165	585	250
8.3-24	TT	66.5	W7	6PR	1050	210	1135	270
8.3-24	TT	66.5	W7	8PR	1265	210	1325	320
12.4-26	TT	72.0	W11	8PR	1245	315	2010	260
☆13.6-24	TT	75.0	W12	10PR	1410	345	2350	250
☆14.9-24	TT	74.0	W13	12PR	1392	378	2250	260
☆14.9-26	TT	82.5	W13	10PR	1465	378	2875	260
14.9-28	TT	85.0	W13L	12PR	1476	378	2120	230
14.9-30	TT	90.0	W13	12PR	1515	378	2430	260
☆16.9-28	TT	84.0	W15L	12PR	1685	430	2580	230
16.9-34	TT	90.0	W15L	10PR	1685	430	3385	220
16.9-34	TT	90.0	W15L	12PR	1755	430	3395	230
18.4-34	TT	90.0	W16L	12PR	1855	467	3590	240
18.4-38	TT	90.0	W16L	12PR	1900	467	3575	230
☆20.8-38	TT	95.0	W18L	12PR		528	4000	200



PORT TIRE SERIES

KT618 (E-4)

Product performance :

- Suitable for large-tonnage forklifts, stackers, reach stackers and other port equipment.
- With sturdy body, specially treated bead, wide tread, and deep patterns, this kind of tyre provides strong support and excellent wear resistance and grip, generate low heat, and ensures a long service life.



Size	Tube Type	PR	Rim	Pattern Depth (mm)	New Tire Inflation Size(mm)		Inflation Pressure at Different Speeds(Kpa)		Load Capacity at Different Speeds(Kg)	
					OD	SW	10Km/h	50Km/h	10Km/h	50Km/h
18.00-25	TL	48PR	13.00/2.5	66.0	1675	500	24300	22500	1260	1155

KT619 (E-4)

Product performance :

- Wide and firm ultra-deep pattern in design, low heat, and excellent wear-resistant tread;
- High-performance super-strong nylon body has a strong bearing capacity and high rate of old body renovation;
- Widened blocky tread makes the tire have excellent traction, improving the stability of vehicles. This type of tire is suitable for container lifting vehicles.



Size	Tube Type	PR	Rim	Pattern Depth (mm)	New Tire Inflation Size(mm)		Inflation Pressure at Different Speeds(Kpa)			Load Capacity at Different Speeds(Kg)		
					OD	SW	0Km/h	5Km/h	10Km/h	0Km/h	5Km/h	10Km/h
12.00-20	TT	28PR	8.50	52.0	1175	330	1100	1100	1100	13000	10500	9800
12.00-24	TT	28PR	8.50	54.0	1275	315	1100	1100	1100	17100	13775	10500
14.00-24	TT/TL	28PR	10.00/2.0	59.0	1420	375	1100	1100	1100	18000	14500	13500
18.00-25	TL	44PR	13.00/2.5	67.5	1675	500	1200	1200	1200	32700	26300	24300

KT619C (E-4)

Product performance :

- Wide and firm ultra-deep pattern in design, low heat, and excellent wear-resistant tread;
- High-performance super-strong nylon body has a strong bearing capacity and high rate of old body renovation;
- Widened blocky tread makes the tire have excellent traction, improving the stability of vehicles. This type of tire is suitable for container lifting vehicles.



Size	Tube Type	PR	Rim	Pattern Depth (mm)	New Tire Inflation Size(mm)		Inflation Pressure at Different Speeds(Kpa)			Load Capacity at Different Speeds(Kg)		
					OD	SW	0Km/h	5Km/h	10Km/h	0Km/h	5Km/h	10Km/h
18.00-25	TL	44PR	13.00/2.5	56.0	1675	500	1200	1200	1200	32700	26300	24300

KT62 (E-3)

Product performance :

- Reinforced body brings a strong bearing capacity, and universal classic water wave in design provides superior wear resistance.
- With a long service life, it is suitable for transtainers and gantry cranes.



Size	Tube Type	PR	Rim	Pattern Depth (mm)	New Tire Inflation Size(mm)		Inflation Pressure at Different Speeds(Kpa)			Load Capacity at Different Speeds(Kg)		
					OD	SW	0Km/h	5Km/h	10Km/h	0Km/h	5Km/h	10Km/h
18.00-25	TL	44PR	13.00/2.5	35.0	1615	500	1200	1200	1200	32700	26300	24300
21.00-25	TL	40/44PR	15.00/3.0	43.5	1750	570	1100	1100	1100	38900	31100	21800
21.00-35	TL	40/44PR	15.00/3.0	43.5	2005	570	1200	1200	1200	43700	35200	33800

KT632 (E-3)

Product performance :

- With excellent wear resistance, it can provide a long service life;
- Reinforced tire body provides a strong bearing capacity and excellent traction. It is designed for container transferring vehicles, and AGV at ports.



Size	Tube Type	PR	Rim	Pattern Depth (mm)	New Tire Inflation Size(mm)		Inflation Pressure at Different Speeds(Kpa)			Load Capacity at Different Speeds(Kg)		
					OD	SW	0Km/h	5Km/h	10Km/h	0Km/h	5Km/h	10Km/h
14.00-24	TL	28PR	41/2J	28.0	1375	375	1100	1100	1100	17100	13775	13500

KT620 (E-4)

Product performance :

- Novel I-shape pattern in design brings strong traction;
- Low heat, excellent wear-resistant tread, high-performance and super-strong nylon body, strong bearing capacity, no bulging, no air leakage, long service life
- Blocky widened tread and deepen pattern with a strong lateral force resistance bring excellent traction. This type of tire is designed for container lifting vehicles and AGV at ports.



Size	Tube Type	PR	Rim	Pattern Depth (mm)	New Tire Inflation Size(mm)		Inflation Pressure at Different Speeds(Kpa)			Load Capacity at Different Speeds(Kg)		
					OD	SW	0Km/h	5Km/h	10Km/h	0Km/h	5Km/h	10Km/h
14.00-24	TT/TL	28PR	10.00/2.0	44.0	1370	375	1100	1100	1100	18000	14500	13500
16.00-25	TL	36PR	11.25/2.0	49.5	1495	430	1100	1100	1100	23800	19200	18400
18.00-25	TL	44PR	13.00/2.5	67.5	1675	500	1200	1200	1200	32700	26300	24300

KT100S (L-5S)

Product performance :

- Designed for port machinery, this type of tire has smooth and superdeep patterns.
- Smooth surface enables tires more durable, proving a longerservice life.



Size	Tube Type	PR	Rim	Pattern Depth (mm)	New Tire Inflation Size(mm)		Inflation Pressure at Different Speeds(Kpa)			Load Capacity at Different Speeds(Kg)		
					OD	SW	0Km/h	5Km/h	10Km/h	0Km/h	5Km/h	10Km/h
18.00-25	TL	44PR	13.00/2.5	87.0	1675	500	1200	1200	1200	32700	26300	24300

KT620C (E-4)

Product performance :

- Novel I-shape pattern in design brings strong traction;
- Low heat, excellent wear-resistant tread, high-performance and super-strong nylon body, strong bearing capacity, no bulging, no air leakage, long service life
- Blocky widened tread and deepen pattern with a strong lateral force resistance bring excellent traction. This type of tire is designed for container lifting vehicles and AGV at ports.



Size	Tube Type	PR	Rim	Pattern Depth (mm)	New Tire Inflation Size(mm)		Inflation Pressure at Different Speeds(Kpa)			Load Capacity at Different Speeds(Kg)		
					OD	SW	0Km/h	5Km/h	10Km/h	0Km/h	5Km/h	10Km/h
18.00-25	TL	44PR	13.00/2.5	56.0	1675	500	1200	1200	1200	32700	26300	24300



INDUSTRIAL VEHICLE TIRE SERIES

KT216

Product performance

•Excellent wear resistance, deep pattern in design, strong bearing capacity, and strong resistance to distortion.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Maximum Tire Load at Different Top Speeds(Kg)								Inflation Pressire (kpa)
							Counter-balanced forklift Truck				Industrial vehicle				
					25km/h		35km/h								
					OD	SW	Driving Wheel	Steering Wheel	Driving Wheel	Steering Wheel	10km/h	25km/h	40km/h	50km/h	
5.00-8NHS	TT	13.5	3.50D	8PR	470	137	1000	845	930	745	845	625	555	535	790
5.00-8NHS	TT	13.5	3.50D	10PR	470	137	1150	970	1065	850	/	/	/	/	1000
6.00-9NHS	TT	12.5	4.00E	10PR	540	160	1505	1275	1400	1120	1275	940	835	805	860
6.50-10NHS	TT	15.5	5.00F	10PR	590	175	1655	1400	1540	1230	1400	1030	920	885	790
7.00-12NHS	TT	16.5	5.00S	12PR	676	190	2375	2005	2205	1765	2005	1480	1320	1265	860
28×9-15NHS	TT	17.5	7.0	12PR	710	220	2790	2355	2590	2070	2355	1735	1550	1485	830
8.25-15NHS	TT	18.5	6.5	12PR	840	235	3490	2945	3240	2590	2945	2170	1940	1860	720

KT218

Product performance

•Excellent wear resistance, deep pattern in design, strong bearing capacity, and strong resistance to distortion.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Maximum Tire Load at Different Top Speeds(Kg)								Inflation Pressire (kpa)
							Counter-balanced forklift Truck				Industrial vehicle				
					OD	SW	25km/h		35km/h		10km/h	25km/h	40km/h	50km/h	
							Driving Wheel	Steering Wheel	Driving Wheel	Steering Wheel					
6.00-9NHS	TT	14.0	4.00E	12PR	540	160	1675	1415	1560	1245	1415	1045	930	895	1030
6.50-10NHS	TT	17.0	5.00F	12PR	590	175	1895	1600	1765	1410	/	/	/	/	1000
7.00-12NHS	TT	17.5	5.00S	14PR	676	190	2590	2190	2405	1925	2190	1610	1440	1380	1000
28×9-15NHS	TT	19.0	7.0	14PR	710	220	3050	2575	2835	2265	2575	1900	1695	1625	970
18×7-8NHS	TT	13.6	4.33R	14PR	465	173	1505	1270	1400	1120	/	/	/	/	970
7.00-9NHS	TT	13.5	5.00S	10PR	590	190	1995	1685	1850	1480	1685	1240	1105	1065	860
8.25-20NHS	TT	16.0	6.5	14PR	974	235	4575	3865	4250	3395	3865	2845	2540	2440	830
9.00-20NHS	TT	19.5	7.0	16PR	1018	259	5595	4725	5200	4155	4725	3480	3110	2985	860
250-15NHS	TT	19.0	7.5	16PR	735	250	3865	3265	3500	2870	3265	2405	2145	2060	930
300-15NHS	TT	20.5	8.0	20PR	840	300	5490								930

KT219

Product performance

•Excellent wear resistance, deep pattern in design, strong bearing capacity, and strong resistance to distortion.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Maximum Tire Load at Different Top Speeds(Kg)								Inflation Pressire (kpa)
							Counter-balanced forklift Truck				Industrial vehicle				
					25km/h		35km/h								
					OD	SW	Driving Wheel	Steering Wheel	Driving Wheel	Steering Wheel	10km/h	25km/h	40km/h	50km/h	
23X9-10NHS	TT	15.5	6.50F	12PR	595	225	2345	1980	2175	1740	1980	1460	1300	1250	760
27X10-12NHS	TT	14.5	8.00G	12PR	690	255	2970	2505	2755	2205	2505	1845	1650	1585	720

KT220

Product performance



- Unique pattern design, excellent wear resistance, strong bearing capacity, and strong resistance to distortion.

Size	Tube Type	Tread Depth(mm)	Rim	PR	New fire size(mm)		Maximum Tire Load at Different Top Speeds(Kg)								Inflation Pressire (kpa)		
							Counter-balanced forklift Truck				Industrial vehicle						
					25km/h		35km/h		10km/h		25km/h		40km/h			50km/h	
6.50-10NHS	TT	18.0	6.50F	12PR	590	175	1895	1600	1765	1410	/	/	/	/	1000		
28×9-15NHS	TT	19.5	7.0	16PR	710	220	3115	2630	2895	2310	2630	1940	1730	1660	970		



KT228

Product performance



- Deepened patterns in design, excellent wear resistance, strong bearing capacity, and longer service life.
- With anti-friction flanged design in side, this type of tire can be used in hard or extremely harsh conditions to prevent tire side from being punctured or scratched.

Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Maximum Tire Load at Different Top Speeds(Kg)								Inflation Pressire (kpa)
							Counter-balanced forklift Truck				Industrial vehicle				
					25km/h		35km/h		10km/h	25km/h	40km/h	50km/h			
					OD	SW	Driving Wheel	Steering Wheel					Driving Wheel	Steering Wheel	
6.50-10NHS	TT	31.5	5.00F	12PR	590	175	1895	1600	1765	1410	2190	1610	1440	1380	1000
7.00-12NHS	TT	33.0	5.00S	14PR	676	190	2590	2190	2405	1925	/	/	/	/	1000
28×9-15NHS	TT	28.0	7.0	16PR	720	220	3115								1000
8.25-15NHS	TT	32.0	6.5	16PR	840	225	4050	3450	3600	3010	3450	2520	2250	2160	925
8.25-20NHS	TT	33.5	6.5	18PR	974	235	5300								950
250-15NHS	TT	32.5	7.5	20PR	735	250	4580								1000
300-15NHS	TT	30.5	8.0	22PR	840	300	7155								1030



KT28

Product performance



- Wide tread surface and large blocky pattern design provide super wear resistance, cutting resistance, and puncture resistance.

Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Maximum Tire Load at Different Top Speeds(Kg)								Inflation Pressire (kpa)
							Counter-balanced forklift Truck				Industrial vehicle				
					25km/h		35km/h								
					OD	SW	Driving Wheel	Steering Wheel	Driving Wheel	Steering Wheel	10km/h	25km/h	40km/h	50km/h	
9.00-20NHS	TT	26.0	7.0	20PR	1018	259	Load of a single tire:3350kg, air pressure: 910kpa, load of two tires: 2900kg, air pressure 840kpa								860



KT017

Product performance :



- Super wear resistance, deep pattern, strong bearing capacity, and excellent bursting resistance.

Size	Tube Type	Rim	Tread Depth(mm)	New tire size(mm)		Load Capacity(Kg)			
						Counter-balanced forklift Truck		Industrial vehicle	
				OD	SW	10km/h Steering Wheel	25km/h Steering Wheel	10km/h	25km/h
5.00-8/3.50D	/	3.00D-8	22.5	469	146	1255	1060	960	815
6.00-9/4.00	/	4.00E-9	23.3	545	160	1975	1675	1520	1290
6.50-10/5.00	/	5.00F-10	25.0	597	178	2715	2310	2095	1775
7.00-12/5.00	/	5.00S-12	29.0	683	192	3105	2635	2390	2025
8.25-15/6.50	/	6.50-15	35.0	847	236	5085	4310	3910	3315
28X9-15/7.0	/	7.00-15	29.0	706	225	4060	3445	3125	2650
18X7-8/4.33R	/	4.33R-8	20.0	457	170	2430	2060	1870	1585
300-15/8.00	/	8.0-15	33.0	838	300	6895	5850	5310	4500
9.00-20/7.00	/	7.0-20	37.5	1038	259	6365	5400	4905	4500
16X6-8/4.33	/	4.33R-28	15.5	418	162	1545	1190	1185	1005
21X8-9/6.00	/	6.00E-9	22.5	535	207	2890	2645	2230	1890



KT019

Product performance :



- Super wear resistance, deep pattern, strong bearing capacity, and excellent bursting resistance;
- Fast assembly can meet customers' requirements.

Size	Tube Type	Rim	Tread Depth(mm)	New tire size(mm)		Load Capacity(Kg)			
						Counter-balanced forklift Truck		Industrial vehicle	
				OD	SW	10km/h Steering Wheel	25km/h Steering Wheel	10km/h	25km/h
18X7-8/4.33R	/	4.33R-8	20.0	457	170	2430	2060	1870	1585
200/50-10/6.50	/	6.50F-10	15.0	460	221	2910	2240	2440	1900
140/55-9/4.00	/	4.00E-09	9.0	375	147	1380	1170	1060	900
23X9-10/6.50	/	6.50F-10	18.0	595	225	3730	3405	2865	2430
15X4.5-8/3.00	/	3.00D-8	10.0	380	114	1005	915	775	655





CONSTRUCTION MACHINERY TIRE SERIES

KT62 (E-3/L-3)

Product performance :

- Water wave-shaped pattern provides a strong grip and a high drive force.
- Excellent wear resistance and tearing resistance.



Size	Tube Type	Tread Depth (mm)	Rim	PR	New tire Inflation size(mm)		Load Capacity at Different Speeds(kg)		Inflation Pressure at Different Speeds (kpa)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
17.5-25	TT/TL	27.5	14.00/1.5	20PR	1350	445	8250	5000	575	400
17.5-25	TT/TL	27.5	14.00/1.5	24PR	1350	445	8500	5500	600	450
20.5-25	TT/TL	34.0	17.00/2.0	20PR	1490	520	9500	6000	450	325
20.5-25	TT/TL	34.0	17.00/2.0	24PR	1490	520	10300	6700	525	400
23.5-25	TT/TL	35.0	19.50/2.5	20PR	1615	595	10900	7300	375	300
23.5-25	TT/TL	35.0	19.50/2.5	24PR	1615	595	12500	8000	475	350
26.5-25	TT	40.0	22.00/3.0	24PR	1750	675	14000	9250	400	300
26.5-25	TT/TL	40.0	22.00/3.0	28PR	1750	675	15500	10000	475	350

KT622 (E-3/L-3)

Product performance :

- Water wave-shaped pattern provides a strong grip and a high driv force.
- Excellent wear resistance and tearing resistance.



Size	Tube Type	Tread Depth (mm)	Rim	PR	New tire Inflation size(mm)		Load Capacity at Different Speeds(kg)		Inflation Pressure at Different Speeds (kpa)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
23.5-25	TT	35.0	19.50/2.5	18PR	1615	595	10200	7300	350	300
23.5-25	TT	35.0	19.50/2.5	20PR	1615	595	10900	7300	375	300
23.5-25	TT	35.0	19.50/2.5	24PR	1615	595	12500	8000	475	350

KT62C (E-3/L-3)

Product performance :

- Water wave-shaped pattern provides a strong grip and a high drive force.
- Excellent wear resistance and tearing resistance.



Size	Tube Type	Tread Depth (mm)	Rim	PR	New tire Inflation size(mm)		Load Capacity at Different Speeds(kg)		Inflation Pressure at Different Speeds (kpa)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
17.5-25	TT	24.0	14.00/1.5	24PR	1350	445	8500	5500	600	450
20.5-25	TT	31.0	17.00/2.0	24PR	1490	520	10300	6700	525	400
23.5-25	TT	32.5	19.50/2.5	24PR	1615	595	12500	8000	475	350

KT625 (E-3/L-3)

Product performance :

- Strong grip force, high driving force, excellent wear resistance and tear resistance.
- With strong bearing capacity, this type of tire can cope with a variety of road conditions.



Size	Tube Type	Tread Depth (mm)	Rim	PR	New tire Inflation size(mm)		Load Capacity at Different Speeds(kg)		Inflation Pressure at Different Speeds (kpa)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
23.5-25	TT	32.5	19.50/2.5	16PR	1615	595	300	225	9500	6150
23.5-25	TT	32.5	19.50/2.5	18PR	1615	595	350	300	10200	7300

KT620 (L-5)

Product performance :

- I-shaped pattern improves the traction and lateral force of tires, ultra-deep pattern design, good driving and braking, longer service life.
- The thickened body improves the impact resistance and puncture resistance of tires.



Size	Tube Type	Tread Depth (mm)	Rim	PR	New tire Inflation size(mm)		Load Capacity at Different Speeds(kg)		Inflation Pressure at Different Speeds (kpa)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
23.5-25	TT	76.0	19.50/2.5	40PR	1615	595	750	600	18000	12000

KT630 (E-4)

Product performance :

- Thickened bottom adhesive of pattern grooves provide super puncture resistance, strong gripping force and high driving performance;
- Multi-groove shoulder in design can disperse heat, and cannot peel off. With excellent wear resistance, this type of tire is suitable for bad roads of mines, construction sites and stock grounds.



Size	Tube Type	Tread Depth (mm)	Rim	PR	New tire Inflation size(mm)		Load Capacity at Different Speeds(kg)		Inflation Pressure at Different Speeds (kpa)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
23.5-25	TT	50.0	19.50/2.5	28PR	1615	595	550	400	13600	8750

KT619 (E-3)

Product performance :

- Excellent puncture resistance, gripping force and wear resistance;
- Changing groove angle improves the traction force and lateral force of tires.
- New body structure enhances impact resistance and fatigue resistance of tires, so this type of tire is suitable for bad roads of mines, construction sites, and stock grounds, etc.



Size	Tube Type	Tread Depth (mm)	Rim	PR	New tire Inflation size(mm)		Load Capacity at Different Speeds(kg)		Inflation Pressure at Different Speeds (kpa)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
23.5-25	TT	42.5	19.50/2.5	40PR	1615	595	750	600	18000	12000

IB9 (E-3/L-3)

Product performance :

- Water wave-shaped pattern provides a strong grip and a high drive force.
- Excellent wear resistance and tearing resistance.



Size	Tube Type	Tread Depth (mm)	Rim	PR	New tire Inflation size(mm)		Load Capacity at Different Speeds(kg)		Inflation Pressure at Different Speeds (kpa)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
17.5-25	TT/TL	27.5	14.00/1.5	24PR	1350	445	600	450	8500	5500
23.5-25	TT	35.0	19.50/2.5	18PR	1615	595	350	300	10200	7300
23.5-25	TT	35.0	19.50/2.5	20PR	1615	595	375	300	10900	7300

KT100S (L-5S)

Product performance :

- Widened crown, excellent puncture resistance, strong bearing capacity, superior adaptability in harsh environments;
- Smooth surface makes tires more wear-resistant, providing longer service life. This type of tire is suitable for use in tunnels, and underground mines.



Size	Tube Type	Tread Depth (mm)	Rim	PR	New tire Inflation size(mm)		Load Capacity at Different Speeds(kg)		Inflation Pressure at Different Speeds (kpa)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
☆10.00-20	TT	34	7.5	20PR	1073	278	910	/	5600	/
12.00-24	TT	58	8.5	24PR	1245	315	975	750	7500	5770
17.5-25	TT/TL	65	14.00/1.5	20PR	1350	445	575	400	8250	5000
17.5-25	TT/TL	65	14.00/1.5	24PR	1350	445	600	450	8500	5500
26.5-25	TT	100	22.00/3.0	△36PR	1750	675	925	625	18500	13500

KT777 (C-2)

Product performance :

- Large classic blocky roller patterns in design;
- Wide tread brings excellent wear resistance and puncture resistance, providing longer service life.



Size	Tube Type	Tread Depth (mm)	Rim	PR	New tire Inflation size(mm)		Load Capacity at Different Speeds(kg)		Inflation Pressure at Different Speeds (kpa)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
23.1-26	TT	18.0	DW20	12PR	1500	595	200	170	5780	3655
23.1-26	TT	18.0	DW20	16PR	1500	595	260	170	6150	3655

KT777A (C-2)

Product performance :

- The diamond-shaped tread in design provides high wear resistance, strong puncture resistance and a longer service life.



Size	Tube Type	Tread Depth (mm)	Rim	PR	New tire Inflation size(mm)		Load Capacity at Different Speeds(kg)		Inflation Pressure at Different Speeds (kpa)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
23.1-26	TL	18.0	Dw20	16PR	1500	595	260	170	6150	3655

KT620 (E/L-4)

Product performance :

- I-shaped pattern improves the traction and lateral force of tires, ultra-deep pattern design, good driving and braking, longer service life.
- The thickened body improves the impact resistance and puncture resistance of tires.



Size	Tube Type	Tread Depth (mm)	Rim	PR	New tire Inflation size(mm)		Load Capacity at Different Speeds(kg)		Inflation Pressure at Different Speeds (kpa)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
26.5-25	TT	54.5	22.00/3.0	32PR	1750	675	550	425	17000	11200
26.5-25	TT	54.5	22.00/3.0	36PR	1750	675	750	675	24200	18200

KT755 (G-2/L-2)

Product performance :

- Tread pattern is directional, providing more effective driving force and grip force;
- With good traction, it is suitable for soft land, sandy land, etc.



Size	Tube Type	Tread Depth (mm)	Rim	PR	New tire Inflation size(mm)		Load Capacity at Different Speeds(kg)		Inflation Pressure at Different Speeds (kpa)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
13.00-24	TT	24.5	8.00	16PR	1280	335	600	-	6500	-
13.00-24	TT	24.5	8.00	18PR	1280	335	670	-	7000	-
14.00-24	TT	25.0	8.00	16PR	1350	360	550	375	7300	3650
14.00-24	TL	24.0	8.00	16PR	1350	360	550	375	7300	3650
17.5-25	TL	25.0	14.00/1.5	16PR	1350	445	-	275	-	3350

KT62

Product performance :

- With wide tread and rough pattern provide good traction, cutting resistance, tear resistance, puncture resistance, wear resistance and self-cleaning performance.



Size	Tube Type	Tread Depth (mm)	Rim	PR	New tire Inflation size(mm)		Load Capacity at Different Speeds(kg)		Inflation Pressure at Different Speeds (kpa)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
☆12.00-16	TT	16.5	6.50H	16PR	865	250	450	350	3190	2000
☆14/90-16	TT	17.5	6.50H	14PR	900	260	700	630	2650	1500
☆20.5/70-16	TT	20.0	8.50	14PR	935	325	450	350	3000	1995
16/70-20	TT	26.5	13(SDC)	14PR	1075	410	450	350	5150	3350
16/70-24	TT	20.5	13(SDC)	14PR	1175	410	450	350	5600	3350
☆16/70-16	TT	17.5	6.50H	14PR	880	280	350	-	1500	-
8.25-16	TT	14.0	6.50H	14PR	865	235	800	-	2300	-
7.50-16	TT	17.5	6.00G	14PR	815	215	720	-	2600	-

KT625 (L-3)

Product performance :

- With optimized and beautiful pattern in design, a strong grip force and self-cleaning performance, this type of tire is suitable for small wheeled excavators.
- With wear-resisting tread and excellent cutting resistance and patterns designed for large engineering, this type of tire enables construction machinery to work normally under various conditions.



Size	Tube Type	Tread Depth (mm)	Rim	PR	New tire Inflation size(mm)		Load Capacity at Different Speeds(kg)		Inflation Pressure at Different Speeds (kpa)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
☆20.5/70-16	TT	20.0	8.50	14PR	935	325	450	350	3000	1995
16/70-20	TT	26.5	13(SDC)	14PR	1075	410	450	350	5150	3350
16/70-24	TT	20.5	13(SDC)	14PR	1175	410	450	350	5600	3350

KT627 (L-3)

Product performance :

•With optimized and beautiful pattern in design, a strong grip force and self-cleaning performance, this type of tire is suitable for small wheeled excavators. Characterized by low heat generation and excellent cutting resistance, the tire can not only meet the requirements for fast running on good roads, but also adapt to bad roads.



Size	Tube Type	Tread Depth (mm)	Rim	PR	New tire Inflation size(mm)		Load Capacity at Different Speeds(kg)		Inflation Pressure at Different Speeds (kpa)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
☆9.00-20	TT	23.0	7.0	16PR	1045	280	860	-	5595	-
☆10.00-20	TT	19.0	7.5	16PR	1055	278	790	-	6030	-



KT628

Product performance :

•With optimized and beautiful pattern in design, a strong grip force and self-cleaning performance, this type of tire is suitable for small wheeled excavators.

•Characterized by low heat generation and excellent cutting resistance, the tire can not only meet the requirements for fast running on good roads, but also adapt to bad roads.



Size	Tube Type	Tread Depth (mm)	Rim	PR	New tire Inflation size(mm)		Load Capacity at Different Speeds(kg)		Inflation Pressure at Different Speeds (kpa)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
☆9.00-16	TL	23.0	6.50H	12PR	890	245	420		1650	

KT755 (R-4)

Product performance :

•Specially designed for small excavators, the pattern provides tires with a strong grip force and good self-cleaning performance, excellent puncture resistance and wear resistance, so that tires have good performance in any road conditions.



Size	Tube Type	Tread Depth (mm)	Rim	PR	New tire Inflation size(mm)		Load Capacity at Different Speeds(kg)		Inflation Pressure at Different Speeds (kpa)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
19.5L-24	TL	31.0	DW16L	14PR	1314	495	230(40km/h)		3450(40km/h)	
19.5L-24	TL	31.0	DW16L	16PR	1314	495	240(40km/h)		3540(40km/h)	
☆12-16.5	TL	17.0	9.75	14PR	831	307	620		3075	
☆10-16.5	TL	17.0	8.25	14PR	773	264	720		2750	
26×12.00-12	TL	16.0	10.50	8PR	648	307	340		1370	
20.5/70-16	TT	15.5	10.00F	16PR	935	325	410		2120/3075	
16.9-24	TL	25.0	W15L	14PR	1309	429	310(44PSI)		3540(8155LBS)	
16.9-28	TL	25.0	W15L	14PR	1435	430	300(44PSI)		3700(8155LBS)	
14-17.5	TL	26.5	10.50	14PR	921	349	550		3875	
21L-24	TL	24.5	DW18L	16PR	1400	533	280		4500	
12.5/80-18	TL	24.0	W9	16PR	985	308	490		3150	
☆20.5/65-16	TT	13.0	9.5	14PR	810	330	450(10Km/h)	350(50Km/h)	3000(10Km/h)	1995(50Km/h)



TRUCK TIRE SERIES

KT11

Product performance :

•With deepened pattern, widened crown, reinforced body, excellent wear resistance, and longer service life, this type of tire is suitable for highway transportation.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
12.00-20	TT	15.0	8.5	18R	1145	315	3750	3350	810	740

KT13

Product performance :

•With deepened pattern, widened crown, reinforced body, excellent wear resistance, and longer service life, this type of tire is suitable for highway transportation.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
11.00-20	TT	15.0	8.0	18PR	1105	293	3650	3150	910	840
10.00-20	TT	15.5	7.5	18PR	1073	278	3350	2900	910	840
9.00-20	TT	15.5	7.0	14PR	1038	259	2575	2300	770	700

T17

Product performance :

•With deepened pattern, widened crown, reinforced body, excellent wear resistance, and longer service life, this type of tire is suitable for highway transportation.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
12.00-20	TT	17.0	8.5	20 PR	1145	315	4000	3450	880	810

T17A

Product performance :

•With deepened pattern, widened crown, reinforced body, excellent wear resistance, and longer service life, this type of tire is suitable for highway transportation.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
14.00-20	TT	20.0	10.0	20 PR	1265	375	5000	4375	770	700

KT24

Product performance :

- With a strong grip force and excellent wear resistance, this type of tire is suitable for poor roads of mines, construction sites, stock yards and roads of mining areas.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
12.00-20	TT	30.0	8.5	22PR	1145	315	4000	3450	880	810
12.00-20	TT	30.0	8.5	18PR	1145	315	3750	3350	810	740
11.00-20	TT	29.0	8.0	22PR	1105	293	3650	3150	910	840
11.00-20	TT	29.0	8.0	18PR	1105	293	3650	3150	910	840
10.00-20	TT	29.0	7.5	18PR	1073	278	3350	2900	910	840
9.00-20	TT	26.5	7.0	16PR	1038	259	2900	2500	880	810

KT245

Product performance :

- With a strong grip force and excellent wear resistance, this type of tire is suitable for poor roads of mines, construction sites, stock yards and roads of mining areas.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
12.00-20	TT	30.0	8.5	22PR	1145	315	4000	3450	880	810
12.00-20	TT	30.0	8.5	18PR	1145	315	3750	3350	810	740
11.00-20	TT	29.0	8.0	22PR	1105	293	3650	3150	910	840
11.00-20	TT	29.0	8.0	18PR	1105	293	3650	3150	910	840

KT77

Product performance :

- With a strong gripping force and excellent wear resistance, this kind of tire is suitable for use on mixed and paved roads.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
11.00-20	TT	21.0	8.0	18 PR	1105	293	3650	3150	910	840
11.00-20	TT	21.0	8.0	16PR	1105	293	3350	2900	810	740

D10B

Product performance :

- With novel pattern, fuel-saving performance, and good self-cleaning performance and without groove cracking, this type of tire is suitable for road transportation.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
12.00-20	TT	15.0	8.5	18PR	1125	315	3750	3350	810	740
11.00-20	TT	15.0	8.0	18PR	1105	293	3650	3150	910	840
10.00-20	TT	15.0	7.5	18PR	1073	278	3350	2900	910	840
9.00-20	TT	14.5	7.0	16PR	1038	259	2900	2500	880	810

KT201

Product performance :

- With deepened patterns, good heat dissipation performance, and a strong body, this kind of tire is suitable for mines, construction sites, and gravel pavement.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
12.00-20	TT	25.0	8.5	20PR	1145	315	4000	3450	880	810
11.00-20	TT	25.0	8.0	18PR	1105	293	3650	3150	910	840
11.00-20	TT	25.0	8.0	16PR	1105	293	3350	2900	810	740
10.00-20	TT	23.0	7.5	18PR	1073	278	3350	2900	910	840
9.00-20	TT	23.0	7.0	16PR	1038	259	2900	2500	880	810

KT235

Product performance :

- With novel pattern, fuel-saving performance, and good self-cleaning performance and without groove cracking, this type of tire is suitable for road transportation.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
11.00-20	TT	17.0	8.0	18PR	1105	293	3650	3150	910	840
11.00-20	TT	17.0	8.0	16PR	1105	293	3350	2900	810	740
10.00-20	TT	17.0	7.5	18PR	1073	278	3350	2900	910	840
10.00-20	TT	17.0	7.5	16PR	1073	278	3000	2650	810	740

KT266

Product performance :

- With deepened pattern, widened crown, reinforced body, excellent wear resistance, and longer service life, this type of tire is suitable for highway transportation.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
10.00-20	TT	18.0	8.5	18 PR	1073	278	3350	2900	910	840

KT622

Product performance :

- With a strong grip force and excellent wear resistance, this type of tire is suitable for poor roads of mines, construction sites, stock yards and roads of mining areas.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
12.00-20	TT	28.5	8.5	22PR	1145	315	4000	3450	880	810
12.00-20	TT	28.5	8.5	18PR	1145	315	3750	3350	810	740
11.00-20	TT	28.5	8.0	22PR	1105	293	3650	3150	910	840
11.00-20	TT	28.5	8.0	18PR	1105	293	3650	3150	910	840
10.00-20	TT	24.0	7.5	18PR	1073	278	3350	2900	910	840
9.00-20	TT	25.0	7.0	16PR	1038	259	2900	2500	880	810

KT623

Product performance :

- With a strong grip force and excellent wear resistance, this type of tire is suitable for poor roads of mines, construction sites, stock yards and roads of mining areas.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
12.00-20	TT	30.0	8.5	22PR	1145	315	4000	3450	880	810
12.00-20	TT	30.0	8.5	18PR	1145	315	3750	3350	810	740
11.00-20	TT	29.0	8.0	22PR	1105	293	3650	3150	910	840
11.00-20	TT	29.0	8.0	18PR	1105	293	3650	3150	910	840

KT688

Product performance :

- With deepened pattern, widened crown, reinforced body, excellent wear resistance, and longer service life, this type of tire is suitable for highway transportation.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
10.00-20	TT	22.0	7.5	18 PR	1073	278	3350	2900	910	840
10.00-20	TT	22.0	7.5	16 PR	1073	278	3000	2650	810	740

T19

Product performance :

- Directional herringbone high drive pattern design, combined with large shoulder design, enhances the vehicle's drive in mud and snow fields;
- Strengthened tire sidewall protection design can effectively prevent scratches on the side during off-road use;
- Strong driving force and road holding, and excellent wear resistance. life, this type of tire is suitable for highway transportation.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)	Inflation Pressire(kpa)
					OD	SW		
13-20	TT	26.5	11.00V	16 PR	1205	395	3750	420



ENGINEERING TRUCK TIRE SERIES

KT62

Product performance :

- With unique pattern design, a strong grip, and superior wear resistance, this type of tire is suitable for pavements of mines, construction sites, gravel yards, etc.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New Tire Iiflation size(mm)		Inflation Pressure at Different Speeds(kpa)		Load Capacity at Different Speeds(kg)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
14.00-24	TT	35.0	10.00/2.0	24PR	1370	375	850	575	9500	5150
14.00-24	TT	35.0	10.00/2.0	36PR	1370	375	1175	865	11100	6600
13.00-25	TT	27.5	8.50	28PR	1300	350	740	740	5570	5510
13.00-25	TT	27.5	8.50	36PR	1300	350	810		7500	

KT599A

Product performance :

- With super wear-resistant rubber tread, unique pattern design, reinforced body, excellent wear resistance, this type of tire is suitable for poor roads of mines, construction sites, stock yards, etc.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New Tire Iiflation size(mm)		Inflation Pressure at Different Speeds(kpa)		Load Capacity at Different Speeds(kg)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
13.00-25	TT	27.5	8.50	32PR	1300	350	750		6000	
13.00-25	TT	27.5	8.50	36PR	1300	350	810		7500	
14.00-25	TT	34.0	10.00/2.0	△36+PR	1370	375	1200	850	11500	6500
14.00-25	TT	34.0	10.00/2.0	40PR	1370	375	1200	850	11500	6500

KT699

Product performance :

- With unique pattern design, a strong grip, and superior wear resistance, this type of tire is suitable for pavements of mines, construction sites, gravel yards, etc.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New Tire Iiflation size(mm)		Inflation Pressure at Different Speeds(kpa)		Load Capacity at Different Speeds(kg)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
14.00-24	TT	32.0	10.00/2.0	24PR	1370	375	850	575	9500	5150
14.00-24	TT	32.0	10.00/2.0	32PR	1370	375	1050	750	10900	6150
13.00-25	TT	27.5	8.50	28PR	1300	350	740	740	5570	5510
13.00-25	TT	27.5	8.50	32PR	1300	350	750		6000	

KT632

Product performance :

•With deep patterns, a strong grip, and superior wear resistance, this type of tire is suitable for poor pavements of mines, construction sites, gravel yards, etc.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New Tire Iflation size(mm)		Inflation Pressure at Different Speeds(kpa)		Load Capacity at Different Speeds(kg)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
14.00-24	TT	31.0	10.00/2.0	24PR	1370	375	850	575	9500	5150
14.00-24	TT	31.0	10.00/2.0	36PR	1370	375	1175	865	11100	6600
13.00-25	TT	27.5	8.50	28PR	1300	350	750		6000	
13.00-25	TT	27.5	8.50	32PR	1300	350	810		7500	
14.00-25	TT	29.5	10.00/2.0	36PR	1370	375	1200	850	11500	6500
14.00-25	TT	29.5	10.00/2.0	40PR	1370	375	1200	850	11500	6500
16.00-25	TT	32.0	11.25/2.0	36PR	1495	430	975	725	13600	7750
16.00-25	TT	32.0	11.25/2.0	40PR+	1495	430	1350	1050	13800	8000

KT798

Product performance :

•With a strong grip force and superior wear resistance, this type of tire is suitable for poor pavements of mines, construction sites, stock grounds, etc.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New Tire Iflation size(mm)		Inflation Pressure at Different Speeds(kpa)		Load Capacity at Different Speeds(kg)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
14.00-25	TT	28.5	10.00/2.0	36+PR	1370	375	1200	850	11500	6500
14.00-25	TT	28.5	10.00/2.0	40PR	1370	375	1200	850	11500	6500

KT626

Product performance :

•With off-road pattern design, strong puncture resistance, superior trafficability, this type of tire is suitable for all kinds of bad roads.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New Tire Iflation size(mm)		Inflation Pressure at Different Speeds(kpa)		Load Capacity at Different Speeds(kg)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
☆16.00-20	TT	22.5	12.0-20	28PR	1310	420	/	650	/	5600

KT698

Product performance :

•With a strong grip force and superior wear resistance, this type of tire is suitable for poor pavements of mines, construction sites, stock grounds, etc.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New Tire Iflation size(mm)		Inflation Pressure at Different Speeds(kpa)		Load Capacity at Different Speeds(kg)	
					OD	SW	10km/h	50km/h	10km/h	50km/h
14.00-20	TT	25.0	10.0	20++PR	1265	375	700	525	7500	4375



LIGHT TRUCK TIRE SERIES

KT11

Product performance :

•With strong loading resistance and super wear resistance, this type of tire is economic, and is suitable for all kinds of good roads.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
6.50-16LT	TT	10.0	5.50F	12PR	750	185	1060	925	630	630

KT13

Product performance :

•With strong loading resistance and super wear resistance, this type of tire is economic, and is suitable for all kinds of good roads.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
8.25-16LT	TT	12.0	6.50H	14PR	855	235	1700	1500	630	630
7.00-16LT	TT	12.0	5.50F	12PR	775	200	1215	1060	630	630

KT15

Product performance :

•With novel patterns, non-cracking grooves, super wear resistance, fuel-saving and economical and practical performance, this kind of tire is suitable for various pavements.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
6.50-14LT	TT	10.5	4 1/2J	8PR	705	180	775	690	420	420

KT35

Product performance :

•With strong loading resistance and super wear resistance, this type of tire is economic, and is suitable for all kinds of good roads.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
7.50-16LT	TT	12.0	6.00G	16PR	816	215	1650	1450	830	830
7.00-16LT	TT	11.0	5.50F	16PR	775	200	1400	1250	810	770
6.50-16LT	TT	10.0	5.50F	12PR	750	185	1060	925	630	630

KT36

Product performance :

•With strong loading resistance and super wear resistance, this type of tire is economic, and is suitable for all kinds of good roads.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
8.25-16LT	TT	12.0	6.50H	16PR	855	235	1800	1600	730	730
7.00-16LT	TT	11.0	5.50F	14PR	775	200	1320	1180	730	730
6.50-14LT	TT	10.0	4 1/2J	8++PR	705	180	775	690	420	420

KT39

Product performance :

•With novel and stylish curved patterns in design, blended fine grooves, beautiful appearance and excellent wear resistance, this kind of tyre is suitable for various paved roads.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
7.50-16LT	TT	13.0	6.00G	14PR	805	215	1500	1320	730	730
7.50-15LT	TT	13.0	6.00G	14PR	780	215	1450	1285	730	730
7.00-16LT	TT	11.0	5.50F	14PR	775	200	1320	1180	730	730

KT42

Product performance :

•With strong loading resistance and super wear resistance, this type of tire is economic, and is suitable for all kinds of good roads.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
7.00-15LT	TT	12.0	5.50F	12 PR	750	200	1150	1030	630	630

KT45

Product performance :

•With novel patterns, non-cracking grooves, super wear resistance, fuel-saving and economical and practical performance, this kind of tire is suitable for various pavements.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
7.00-15LT	TT	11.0	5.50F	12 PR	750	200	1150	1030	630	630

KT117

Product performance :

•With novel patterns, non-cracking grooves, super wear resistance, fuel-saving and economical and practical performance, this kind of tire is suitable for various pavements.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
6.50-14LT	TT	13.0	4 1/2J	10PR	705	180	900	800	530	530

KT118

Product performance :

- With a strong grip force and superior wear resistance, this type of tire is suitable for poor pavements of mines, construction sites, stock grounds and mining areas.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
8.25-16LT	TT	19.0	6.50G	16PR	855	235	1800	1600	730	730
7.50-16LT	TT	19.5	6.00G	16PR	816	215	1650	1450	830	830
7.00-16LT	TT	19.0	5.50F	16PR	775	200	1400	1250	810	770
6.50-16LT	TT	19.0	5.50F	12PR	750	185	1060	925	630	630

KT225

Product performance :

- With a strong grip force and superior wear resistance, this type of tire is suitable for poor pavements of mines, construction sites, stock grounds and mining areas.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
8.25-16LT	TT	18.5	6.50H	16PR	855	235	1800	1600	730	730
7.50-16LT	TT	17.5	6.00G	16PR	816	215	1650	1450	830	830
7.00-16LT	TT	13.0	5.50F	16PR	775	200	1400	1250	810	770
6.50-16LT	TT	9.0	5.50F	12PR	750	185	1060	925	630	630

KT125

Product performance :

- With novel patterns, non-cracking grooves, super wear resistance, fuel-saving and economical and practical performance, this kind of tire is suitable for various pavements.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
6.00-14LT	TT	10.0	4 1/2J	8PR	680	170	690	600	420	420

KT226

Product performance :

- With off-road thick and sturdy patterns, excellent grip and high wear resistance, this kind of tyre is suitable for use on unpaved roads.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
7.50-16LT	TT	17.0	6.00G	14PR	816	215	1500	1320	730	730
7.50-15LT	TT	16.0	6.00G	14PR	780	215	1450	1285	730	730
7.00-16LT	TT	17.0	5.50F	14PR	775	200	1320	1180	730	730

KT235

Product performance :

- With new transverse mixed deepened pattern, a strong loading resistance, and superior wear resistance, this type of tire is suitable for quarries and rural-urban fringes.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
7.50-16LT	TT	13.5	6.00G	16 PR	816	215	1650	1450	830	830
7.50-16LT	TT	13.5	6.00G	14 PR	816	215	1600	1450	810	770

KT623

Product performance :

- With deepened pattern, unique design, a strong loading resistance, and a long service cycle, this type of tire is suitable for poor pavements of mines and construction sites.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
8.25-16LT	TT	25.0	6.50H	16PR	855	235	1800	1600	730	730
7.50-16LT	TT	20.5	6.00G	16PR	816	215	1650	1450	830	830
7.00-16LT	TT	18.5	5.50F	16PR	775	200	1400	1250	810	770

KT588

Product performance :

- With a strong gripping force and excellent wear resistance, this kind of tire is suitable for use on mixed and paved roads.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
7.50-16LT	TT	19.0	6.00G	16 PR	816	215	1650	1450	830	830
7.50-16LT	TT	19.0	6.00G	14 PR	816	215	1600	1450	810	770

KT632

Product performance :

- With a strong grip force and superior wear resistance, this type of tire is suitable for poor pavements of mines, construction sites, stock grounds and mining areas.



Size	Tube Type	Tread Depth(mm)	Rim	PR	New tire size(mm)		Load Capacity(kg)		Inflation Pressire(kpa)	
					OD	SW	Single tire	Double tires	Single tire	Double tires
8.25-16LT	TT	25.0	6.50H	16PR	855	235	1800	1600	730	730
7.50-16LT	TT	25.0	6.00G	16PR	816	215	1650	1450	830	830
7.00-16LT	TT	22.0	5.50F	16PR	775	200	1400	1250	810	770
6.50-16LT	TT	21.5	5.50F	12PR	750	185	1060	925	630	630
6.50-14LT	TT	18.0	4 1/2J	10PR	705	180	900	800	530	530

Industry code for agricultural tires

Purpose	Pattern code	Pattern form	Scope of application
Agricultural tractor (driving wheel)	R-1	Ordinary	Dry field operation, short field transportation
	R-1W	Wetland traction	High soil moisture, short field transportation
	R-2	Sugar cane field and rice field type	Field operation with high soil moisture and mud
	R-3	Flotation	Operation on soft sand soil
	R-4	Industry	Agricultural engineering
Agricultural tractor (guide wheel)	F-1	Single strip	Paddy fields
	F-2	Two or more strips	Tillage and short field transportation
	F-3	Flotation and multi-strips	Sand and loose soil
Agricultural implements	I-1	Multi-strip	Guide wheel and support wheel for agricultural machinery
	I-2	Traction	Driving wheels for agricultural implements
	I-3	Heavy traction	Driving wheels for agricultural implements
	I-4	Plow-tail wheel	Supporting wheel for agricultural implements
	I-5	Guiding type	Dedicated to guide wheels
Forestry machinery	I-6	Flotation	Sand and loose soil
	LS-1	Ordinary	Driving wheels for forestry machinery
	LS-2	Medium-deep	Driving wheels for forestry machinery
High-flotation agriculture implements	LS-3	Ultra-deep	Driving wheels for forestry machinery
	HF-1	High-flotation	High-flotation agricultural implements
	HF-2	High-flotation and ordinary	High-flotation agricultural implements
	HF-3	High-flotation and deepened	High-flotation agricultural implements
Agricultural paddy field tractor Inter-tilling agricultural machinery	HF-4	High-flotation and super deepening	High-flotation agricultural implements
	PR-1	Paddy fields	Paddy fields
	CR-1	Inter-tilling	Field inter-filling

Speed and symbol comparison table

Speed symbol	A1	A2	A3	A4	A5	A6	A7	A8	B	C	D	E	F	G	J
Speed(Km/h)	5	10	15	20	25	30	35	40	50	60	65	70	80	90	100
Speed(Km/h)	3	6	9	12	16	19	22	25	31	37	40	43	50	56	62

A speed symbol indicates the maximum traveling speed corresponding to the rated load and rated air pressure

Industry code for construction machinery tire

Purpose	Pattern code	Pattern form	Type of use	Maximum speed *Km/h	Maximum one-way distance*
Roadroller	C-1	Smooth	Road roller	10	Unlimited
	C-2	Groove	Road roller	10	Unlimited
Carry-scraper Dumper	E-1	Ordinary strip-type	Carrying	65	4Km
	E-2	Ordinary traction	Carrying	65	4Km
	E-3	Ordinary block	Carrying	65	4Km
	E-4	Deepened block	Carrying	65	4Km
	E-7	Flotation	Carrying	65	4Km
Land leveler	G-1	Ordinary strip-type	Land leveling	40	Unlimited
	G-2	Ordinary traction	Land leveling	40	Unlimited
	G-3	Ordinary block	Land leveling	40	Unlimited
	G-4	Deepened block	Land leveling	40	Unlimited
Loader Bulldozer	L-2	Ordinary traction	Loading, bulldozing	10	75m
	L-3	Ordinary block	Loading, bulldozing	10	75m
	L-4	Deepened block	Loading, bulldozing	10	75m
	L-5	Superdeep block	Loading, bulldozing	10	75m
	L-3S	Ordinary smooth surface	Loading, bulldozing	10	75m
	L-4S	Deepened smooth surface	Loading, bulldozing	10	75m
Industrial vehicles	L-5S	Superdeep smooth surface	Loading, bulldozing	10	75m
	IND-3	Ordinary pattern	-	30	Unlimited
	IND-4	Deepended pattern	-	30	Unlimited
	IND-5	Superdeep pattern	-	30	Unlimited

Metric system and British system comparison									
Rim diameter	Specification under British system	85series of tires	80series of tires	75series of tires	70series of tires	65series of tires	60series of tires	50-55series of tires	90-95 series of intertillage tires
16	6.50R16				260/70R16	280/65R16			
	7.50R16		250/80R16		280/70R16	320/65R16			210/95R16:7.50R16
18	7.50R18		250/80R18		280/70R18	320/65R18			210/95R18:7.50R18
20	7.50R20				280/70R20	340/65R18			210/95R20:8.30R20
	9.50R20	250/85R20	260/80R20		300/70R20	340/65R20			
	11.2R20	280/85R20			320/70R20				
	12.4R20	320/85R20	340/80R20	340/75R20	360/70R20	420/65R20			
24		250/85R24			300/70R24				
	8.30R24	280/85R20			320/70R20				
	9.50R24	320/85R20	340/80R20	340/75R20	360/70R20	420/65R20			
		250/85R24			300/70R24				
	11.2R24	280/85R24			320/70R24	440/65R20			
					380/70R20				
	12.4R24	320/85R24			360/70R24	420/65R24			
	13.6R24	340/85R24			380/70R24	440/65R24			210/95R32:8.30R20
					400/70R24				
	14.9R24	380/85R24			420/70R24	480/65R24			230/95R32:9.50R20
26					460/70R24				
	16.9R24	420/85R24			480/70R24	540/65R24			
	14.9R26	380/85R26			380/70R28	540/65R24			
	16.9R26				480/70R26	540/65R26			270/95R32:11.2R32
									230/95R36:9.50R36
	18.4R26				480/70R28	540/65R28	600/60R28	750/50R26	270/95R36:11.2R36
28					580/70R26				230/95R38:9.50R38
	28LR26			620/75R26	600/70R30	750/65R26			
	9.50R28	250/85R28			360/70R24	340/65R28			
	11.2R28	280/85R28			320/70R28	440/65R24			210/95R32:8.30R20
	12.4R28	320/85R28			360/70R28	420/65R28			
	13.6R28	340/85R28			380/70R28	440/65R28	480/60R28		270/95R32:11.2R32
	14.9R28	380/85R28			420/70R28	480/65R28	520/60R28		230/95R36:9.50R36
					480/70R26	540/65R26			
30	16.9R28	420/85R28			480/70R28	540/65R28	600/60R28	750/50R26	270/95R36:11.2R36
					580/70R26				
					600/70R28				
	14.9R30	380/85R30			480/70R28	540/65R28			270/95R36:11.2R36
					420/70R30				
	16.9R30	420/85R30		480/75R30	480/70R30	540/65R30	600/60R30		270/95R38:11.2R38
32						600/65R28			230/95R40:9.50R40
	18.4R30	460/85R30			520/70R30	600/65R30		710/55R30	420/90R30:8.30R44
		320/85R38			600/70R28				
					620/70R26				210/95R44
				620/75R26	600/70R30				
36	9.50R32								230/95R32:9.50R32
	12.4R32	320/85R32							270/95R32:11.2R32
	24.5R32			650/75R32	680/70R32				
				620/75R34					
40	30.5LR32			680/75R32	680/70R34	800/65R32			

Metric system and British system comparison									
Rim diameter	Specification under British system	85series of tires	80series of tires	75series of tires	70series of tires	65series of tires	60series of tires	50-55series of tires	90-95 series of intertillage tires
34	14.9R34	380/85R34							
	16.9R34	420/85R34		400/75R38	480/70R34	540/65R34			230/95R44:9.50R44
	18.4R34	460/85R34		520/75R34	520/70R34	600/65R34			270/95R44:11.2R44
					650/70R30				230/95R48:9.50R48
36			480/80R34		600/70R34				
	11.2R36	320/85R34							270/95R36:11.2R36
	12.4R36	320/85R36		480/75R30	480/70R30	540/65R30	600/60R30		270/95R38:11.2R38
	13.6R36	340/85R36			520/70R30	600/65R30		710/55R30	210/95R44
38		380/85R34			600/70R28				
		460/85R30			620/70R26				
	12.4R38	320/85R38							
	13.6R38	340/85R38		400/75R38	500/70R34	540/65R34			230/95R44:9.50R44
	14.9R38	340/85R38	380/80R38	520/75R34	520/70R34	600/65R34			
		460/85R34							
	16.9R38	420/85R38		620/75R30	480/70R38	540/65R38			230/95R48:9.50R48
	18.4R38	460/85R38	480/80R38	620/75R34	520/70R38	600/65R38	650/60R38		300/95R46:12.4R46
				650/75R32	680/70R32				270/95R48:11.2R48
	20.8R38	520/85R38	480/80R42	680/75R32	580/70R38	650/65R38	710/60R38	900/55R32	320/90R50
			420/80R46		620/70R38	750/65R34	900/60R32	1050/50R32	380/90R46
						800/65R32			
42					710/70R38				
		650/85R38							
	9.50R42	320/85R38							230/95R42
	11.2R42					600/65R34			270/95R42
	18.4R42	460/85R42		680/75R32	580/70R38	600/65R42		900/55R32	320/90R50
		340/85R48			620/70R38	650/65R38		1050/50R32	
	20.8R42	520/85R42	480/80R46	650/75R38	580/70R42	650/65R42	710/60R42	900/50R42	300/95R52:12.4R52
		680/85R32		710/75R34	620/70R42			900/60R32	270/95R54:11.2R54
46					710/70R38				320/90R54
					710/70R42				
				710/75R42					
					520/70R38				270/95R46:11.2R46
	12.4R46	340/85R46							300/95R46
									320/90R46
48	18.4R46		420/80R46						380/90R46
			480/80R46						
	20.8R46	520/85R46	480/80R50		620/70R46	650/65R38	900/60R38		380/90R50
		650/85R38			800/70R38				
50	11.2R48	340/85R48							270/95R48
									420/90R48
52	18.4R50								380/90R50
	12.4R54								320/90R54:270/95R54

Loading capacity table

Load Index	Loading capacity		Load Index	Loading capacity		Load Index	Loading capacity		Load Index	Loading capacity	
	Kg	LBS		Kg	LBS		Kg	LBS		Kg	LBS
100	800	1760	126	1700	3750	152	3550	7830	178	7500	16530
101	825	1820	127	1750	3860	153	3650	8050	179	7750	17090
102	850	1870	128	1800	3970	154	3750	8270	180	8000	17640
103	875	1930	129	1850	4080	155	3875	8540	181	8250	18200
104	900	1980	130	1900	4190	156	4000	8820	182	8500	18740
105	925	2040	131	1950	4300	157	4125	9090	183	8750	19290
106	950	2090	132	2000	4410	158	4250	9370	184	9000	19840
107	975	2150	133	2060	4540	159	4375	9650	185	9250	20390
108	1000	2200	134	2120	4670	160	4500	9920	186	9500	20940
109	1030	2270	135	2180	4810	161	4625	10200	187	9750	21500
110	1060	2340	136	2240	4940	162	4750	10470	188	10000	22050
111	1090	2400	137	2300	5070	163	4875	10750	189	10300	22710
112	1120	2470	138	2360	5200	164	5000	11020	190	10600	23370
113	1150	2540	139	2430	5360	165	5150	11350	191	10900	24060
114	1180	2600	140	2500	5510	166	5300	11690	192	11200	24690
115	1215	2680	141	2575	5680	167	5450	12020	193	11500	25360
116	1250	2760	142	2650	5840	168	5600	12350	194	11800	26020
117	1285	2830	143	2725	6010	169	5800	12790	195	12150	26790
118	1320	2910	144	2800	6170	170	6000	13230	196	12500	27560
119	1360	3000	145	2900	6390	171	6150	13560	197	12850	28330
120	1400	3090	146	3000	6610	172	6300	13890	198	13200	29100
121	1450	3200	147	3075	6780	173	6500	14330	199	13600	29990
122	1500	3310	148	3150	6950	174	6700	14770	200	14000	30870
123	1550	3420	149	3250	7170	175	6900	15210	201	14500	31970
124	1600	3530	150	3350	7390	176	7100	15650	202	15000	33070
125	1650	3640	151	3450	7610	177	7300	16090	203	15500	34180

*Pressure units conversion table

bar	1.0	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5
kpa	100	150	200	250	300	350	400	450	500	550
P.s.i.	15	20	29	36	44	51	58	65	73	80

*Units conversion table

Length	
1 millimeter(mm)	=0.3937"
1 inch(")	=25.4 mm=0.0254 m
1 meter (m)	=3.281 ft
1 foot(ft)	=0.3048m
1 kilometer (km)	=0.6214 mile
1 mile =	1609 m= 1.609 km

Mass	
1 pound (lb)	=0.4536 kg
1 kilogram (kg)	=2.205 lbs

Volume	
1 litre (l)	= 0.21 gall
1 imperial gallon (imp.gal)	= 4.55 l

Pressure	
1 p.s.i. (lb/in2)	= 6.895 kPa
1 kg/cm2	=98.066 kPa
1 bar	= 1 kPa

CORPORATE HONORS

